

IKA® 2012 Best Value



2012 Best Value



C-MAG HS 7 IKAMAG® Package
503,00 €



topolino / topolino mobil IKAMAG®

Extremely convenient mini-stirrer for quantities up to 250 ml.
topolino mobil: portable unit with long operating time (8 - 12 h).

Technical data	
Stirring quantity (H ₂ O)	250 ml
Speed range	30 – 1.800 rpm
Motor rating input/output	1,1/0,8 W

topolino IKAMAG® Ident. No. 3368000
topolino mobil IKAMAG® Ident. No. 3381300

78,00 € 157,00 €



C-MAG HS 7 IKAMAG®

Magnetic stirrer with ceramic heating plate. Bushing according to DIN 12878 for connecting a contact thermometer, e.g. ETS-D5.

Technical data	
Stirring quantity (H ₂ O)	10 l
Speed range	100 – 1.500 rpm
Temperature range	50 – 500 °C
Heat output	1.000 W
Speed-/Temperature display	scale/digital

Ident. No. 3581200

391,00 €



RH basic 2 IKAMAG®

Magnetic stirrer with stainless steel heating plate.

Technical data	
Stirring quantity (H ₂ O)	10 l
Speed range	100 – 2.000 rpm
Temperature range	RT – 320 °C
Heat output	400 W
Speed-/Temperature display	scale (0 – 6)

Ident. No. 3339000

290,00 €



C-MAG HS 7 IKAMAG® Package

Package includes C-MAG HS 7, contact thermometer ETS-D5, support rod H 16 V, holding rod H 38 and boss head clamp H 44.

Technical data	
Stirring quantity (H ₂ O)	10 l
Speed range	100 – 1.500 rpm
Temperature range	50 – 500 °C
Heat output	1.000 W
Speed-/Temperature display	scale/digital

Ident. No. 9015900

503,00 €



T 18 basic ULTRA-TURRAX® Package

Dispersing unit for volumes from 10 to 1.500 ml.
Package includes T 18 basic + dispersing element S 18 N - 19 G.

Technical data	
Volume range (H ₂ O)	10 – 1.500 ml
Speed range	3.500 – 24.000 rpm
Motor rating input/output	500/300 W
Max. viscosity	5.000 mPa·s
Speed display	scale

Ident. No. 9018900

784,00 €



Package without stand and clamps

T 10 standard ULTRA-TURRAX® PCR Kit

Dispersing unit for volumes of 1 to 100 ml. Perfect for PCR tests.
Package includes the unit + clamp R 200 + storage case with dispersing elements S 10 D - 7 G - KS - 65 and S 10 D - 7 G - KS - 110 + set of 12 dispersing elements S 10 D - 7 G - KS - 65.

Technical data	
Volume range (H ₂ O)	1 – 100 ml
Speed range	8.000 – 26.000 rpm
Motor rating input/output	125/75 W
Max. viscosity	5.000 mPa·s
Speed display	scale

Ident. No. 4095500

799,00 €



Package incl. storage case and dispersing elements, without stand



S 10 D - 7 G - KS - 65
Disposable plastic dispersing elements
7 x 65 mm / 12 pcs.

VORTEX 1

New test tube shaker with touch function. Specially for mixing small sample volumes with touch function. Infinitely adjustable speed range.



Technical data	
Shaking motion	orbital
Orbital diameter	4,5 mm
Max. shaken quantity (1 test tube)	100 ml
Motor rating input / output	1,2 / 0,8 W
Speed range	1.000 – 2.800 rpm
Dimensions (W x D x H)	95 x 110 x 70 mm
Weight	0,55 kg

Ident. No. 4047700

217,00 €



VORTEX 4 basic / VORTEX 4 digital

Compact, universal small shaker suitable for shaking tasks with small vessels and microtiter plates.



VORTEX 4 basic
Ident. No. 4049600

295,00 €



VORTEX 4 digital
Ident. No. 4050100

359,00 €

	VORTEX 4 basic	VORTEX 4 digital
Technical data		
Shaking motion	orbital	orbital
Orbital diameter	4,5 mm	4,5 mm
Max. permitted shaking weight (incl. attachment)	0,5 kg	0,5 kg
Motor rating input / output	10 / 8 W	10 / 8 W
Speed range	0 – 3.000 rpm	0 – 3.000 rpm
Operating mode	Continuous / touch operation	Timer and continuous mode, touch operation
Dimensions (W x D x H)	176 x 190 x 63 mm	176 x 190 x 63 mm
Weight	3,0 kg	3,0 kg

IKA® 2012 Best Value

KS 130 & KS 260 Packages – unshakable performance from IKA®



KS 130 basic Package

Small, quiet orbital shaker ensures long life with ideal swivel motion, for a maximum shaking weight of 2 kg. LED display for speed and time.

Technical data	
Shaking motion	orbital
Speed range	80 – 800 rpm
Orbital diameter	4 mm
Max. shaking weight	2 kg
Timer	5 – 50 min

Ident. No. 9019000

784,00 €



STICKMAX Adhesive mat Ident. No. 3920000 AS 130.3 Dish attachment Ident. No. 3120000

KS 130 control Package

Small, quiet orbital shaker ensures long life with ideal swivel motion, for a maximum shaking weight of 2 kg. Digital display for speed and time. Integrated end point positioning and interface RS 232 to control and document automatic processes.

Technical data	
Shaking motion	orbital
Speed range	80 – 800 rpm
Orbital diameter	4 mm
Max. shaking weight	2 kg
Timer	0 – 9 h 59 min
Digital display	speed, time
Interface	RS 232

Ident. No. 9019100

1.106,00 €




STICKMAX Adhesive mat Ident. No. 3920000 AS 130.3 Dish attachment Ident. No. 3120000

STICKMAX

New universal adhesive mat for the fixing clip attachments of KS 130, KS/HS 260, KS/HS 501 and KS 4000 shakers.

- Ideal for frequently changing vessel types and sizes
- Self-adhesive
- Vessels can be easily removed thanks to side fitting movement
- Suitable for disinfection
- Peel-away strength required: 5 N/cm²
- Dimensions (W x D): 200 x 200 mm



KS 260 basic Package

Small, quiet orbital shaker ensures long life with ideal swivel motion, for a maximum shaking weight of 7,5 kg. LED display for speed and time adjustment.

Technical data	
Shaking motion	orbital
Speed range	20 – 500 rpm
Orbital diameter	10 mm
Max. shaking weight	7,5 kg
Timer	5 – 50 min

Ident. No. 9019200

1.078,00 €



2x STICKMAX Adhesive mat Ident. No. 3920000 AS 260.3 Dish attachment Ident. No. 3120600

KS 260 control Package

Small, quiet orbital shaker ensures long life with ideal swivel motion, for a maximum shaking weight of 7,5 kg. Digital display for speed and time. Integrated end point positioning and interface RS 232 to control and document automatic processes.

Technical data	
Shaking motion	orbital
Speed range	10 – 500 rpm
Orbital diameter	10 mm
Max. shaking weight	7,5 kg
Timer	0 – 9 h 59 min
Digital display	speed, time
Interface	RS 232

Ident. No. 9019300


1.402,00 €



2x STICKMAX Adhesive mat Ident. No. 3920000 AS 260.3 Dish attachment Ident. No. 3120600

Shakers accessories (KS 130 / KS 260)

AS 130.1 Universal attachment Ident. No. 8017300 **156,00 €**



AS 130.2 Fixing clip attachment Ident. No. 3115000 **66,00 €**



AS 130.4 Test tube support Ident. No. 3120300 **156,00 €**



AS 260.1 Universal attachment Ident. No. 8017400 **190,00 €**



AS 260.2 Fixing clip attachment Ident. No. 3115500 **99,50 €**



AS 2.1 Fixing clip, 25 ml Ident. No. 1234300 **16,80 €**



AS 2.2 Fixing clip, 50 ml Ident. No. 1234400 **16,80 €**



AS 2.3 Fixing clip, 100 ml Ident. No. 1234500 **16,80 €**



AS 2.4 Fixing clip, 200/250 ml Ident. No. 1234600 **33,00 €**



AS 2.5 Fixing clip, 500 ml Ident. No. 1234700 **33,00 €**



AS 2.6 Fixing clip, 1.000 ml Ident. No. 3819300 **33,00 €**



RW 16 basic

Electronically controlled laboratory stirrer for stirring tasks up to 10 liters.

Technical data	
Stirring quantity (H ₂ O)	10 l
Speed range	40 – 1.200 rpm
Motor rating input/output	75/55 W
Max. viscosity	10.000 mPa·s
Max. torque at chuck	40 Ncm

Ident. No. 2572100

728,00 €

