

## X-tra 70 H

Elmasonic ultrasonic cleaning unit

### Elma Order Nos

Elmasonic X-tra 70 H (230 V)	100 1021
Elmasonic X-tra 70 H (115 V)	on request
Stainless steel lid	100 1476
Stainless steel basket (mm / inch) 276 x 126 x 80 / 10.9 x 5.0 x 3.1	100 1361
Additional accessories on request	



Pictured X-tra 70 H

The extra legue of ultrasonic cleaners “Made in Germany“

- long life through new cavitation-resistant stainless steel, with extended warranty for 3 years
- powerful through additional transducer systems
- Sweep – for optimal sound distribution because of electrical oscillation of the sound field
- 2 cleaning modes: “power“ for intensive cleaning, “soft“ for careful cleaning of sensitive materials
- strong heating power for a short heat-up time
- dry-running proof heating elements
- practical handling through appliance inlet
- fast drainage, with welded pipes
- protected operating panel
- timer for ultrasonic activity, variable between 0 and 15 min. and permanent operation
- temperature control 30 - 80 °C

Technical data			
Mains voltage (Vac)	100-120V oder 200-240V	Tank max. volume (litres)	6,5
Mains connection	1 Ph. / 1N / 1 PE	Drain	3/8“
Ultrasonic frequency (kHz)	35	Weight (kg)	9,6
Power consumption total (W)	600	Material tank	Stainless steel
Ultrasonic power effective (W)	110 / 180	Material casing	Stainless steel
Ultrasonic peak performance max.* (W)	720	Protection class	IP 21
Heating (W)	400		
Power frequency (Hz)	50 / 60		
Unit outer dimensions W / D / H (mm)	360 / 225 / 300		
Tank int. dimensions W / D / H (mm)	300 / 150 / 150		

\* The signal form of the wave results in a factor 4 for the ultrasonic peak max., depending on the modulation of the wave.