

## Data Sheet

Mixing / Magnetic Stirrers



### lab disc white

Ultra-flat compact magnetic stirrer, guaranteed with modern magnet coil technology.  
Wear-free drive with no moving parts. To ensure better mixing, the lab disc can reverse direction of rotation automatically every 30 seconds.

- High IP protection class (IP 65)
- Set-up plate and casing made from chemically resistant materials
- Slip-proof, safe stand

Accessories: TRIKA® 25 Magnetic stirring bar, RSE Stirring bar remover, IKAFLON® 15 Magnetic stirring bar, IKAFLON® 25 Magnetic stirring bar, IKAFLON® 10 Magnetic stirring bar, IKAFLON® 20 Magnetic stirring bar, IKAFLON® 30 Magnetic stirring bar

Imlab  
Oude Vijvers 1  
B-3370 Boutersem

Tel.: +32 16 73 55 72  
Fax: +32 16 73 55 87

[info@imlab.be](mailto:info@imlab.be)  
[www.imlab.be](http://www.imlab.be)

Technical Data	
Number of stirring positions	1
Stirring quantity max. per stirring position (H <sub>2</sub> O) [l]	0.8
Motor rating input [W]	5
Motor rating output [W]	3
Speed range [rpm]	15 - 1500
Stirring bar length max. [mm]	25
Set-up plate material	polyester
Set-up plate dimensions [mm]	Ø 100
Dimensions (W x H x D) [mm]	117 x 12 x 180
Weight [kg]	0.3
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 65
Voltage [V]	100 - 240
Frequency [Hz]	50/60
Power input [W]	5
Ident. No.	3907500